



始于1976

东台市江海救生消防设备有限公司
Dongtai City Jianghai Lifesaving & Fire-fighting
Equipment Limited Company

救生服产品合格证

Immersion Suits Quality Certificate

产品型号 Model	DBF-I(A)	型式认可证书 Certificate of Type Approval	JS20PTB00032_02
制造年月 Date of manufacture	2022年7月	船用证书编号 Cert No. of product	TZ22PPS01844_19
产品编号 No	221091	规格 Size	M <input type="checkbox"/> L <input checked="" type="checkbox"/> XL <input type="checkbox"/>

主要指标 Performance

1	材料 Material	真空镀铝PET薄膜, 聚乙烯泡沫芯材。 Vacuum Aluminium-plated PET Film, Foamed polyethylene.
2	规格 Size	M, 适合身高1.65~1.75米的人员穿着。 M, Suitable height 1.65~1.75m。 L, 适合身高1.75~1.85米的人员穿着。 L, Suitable height 1.75~1.85m。 XL, 适合身高1.85~1.95米的人员穿着。 XL, Suitable height 1.85~1.95m
3	保温性能 Thermal performance	穿着者在水温0~2°C平静水流中, 历时6小时后, 体温降低不超过2°C。 The wearer's body core temperature does not fall more than 2°C after a period of 6h immersion in calm circulating water at a temperature of between 0°C and 2°C.
4	浮力 Buoyancy	≥142N, 在淡水中浸泡24小时后, 其浮力损失<5%。 More than 142N and the decrease of buoyancy is less than 5% after submerging in fresh water for 24 hours.
5	漂浮性能 Floating performance	穿着者在水中仰面浮起, 并保持口部露出水面不小于120mm。 The wearer is capable of floating in face-up and lifting the wearer's mouth the water surface at least 120mm.

本产品符合1974年国际海上人命安全公约及其修正案, 经 MSC.207 (81)、MSC.218 (82) 修正的MSC.48 (66) 《国际救生设备规则》, 经MSC.200(80)、MSC.226(82)和MSC.323 (89) 修正的MSC.81(70) 《经修正的救生设备试验建议》的要求, 准予出厂。

It's in compliance with the provisions of International Convention for the Safety of Life at Sea, MSC.48(66) International Life-saving Appliance Code, as amended by MSC. 207 (81) and MSC.218(82), MSC.81(70) Revised Recommendation on Testing of Life-saving Appliance, as amended by MSC.200(80), MSC.226(82) and MSC.323(89).

检验员 (签字)

Surveyor

检验日期

Date of inspection

